

# GOLD-GOLD CONTACT

FOR TB, CA, ET, SDI, WT, PHE SERIES

## :: HFE01 series High Frequency+Electric Hybrid Slip Rings

#### Features

HFE01 slip rings are 1 channel High Frequency, standard, off-the-shelf. It could support 1 channel High Frequencys(up to 18Ghz) transmitting on 360° rotating, The RF rotary joints are needed wherever high-frequency signals have to be transmitted between a fixed platform and second platform in continuous rotation.Such applications includs traditional radar technology for ai traffic control or anti-missile defence,medical engineering, V-sat and Satcom technology as well as TV camera systems or cable drums that allow sensitive cable to be wound the signal frequency can be DC TO 40GHz. HFE01 are often used with electronic sliprings, call optical-electrical hybrid slipring, transmit power and high speed data.

### **Options(On your request)**

Combine with Power circuits and signal circuits

Parts#	Connector Type		
HFE01-SMA	SMA		
HFE01-N	N-type		

(RF Rotary joints) Specifications						
Max speed	60RPM	Torque	0.1N.m			
Frequency	DC~18Ghz	Insertion loss	0.3dB			
Insertion loss ripple	0.05dB	VSWR	≤1.3			
VSWR ripple	0.05	Start up torque	0.1N.m			
Estimated life cycle	100 million	Housing materia	Stainless steel			
Working temperature	-40 to 85 °C	Storage temperature	-50 to 85 °C			
IP rating	IP 51	Weight	50g			

Part#	Fiber Channel	Current(A)	Voltage(VDC/VAC)					
FBE01 - (available in stock)								
FBE01-S/M-P0610	1	6X10A	440V					
FBE01-S/M-S06	1	6XSignal(2A)	440V					
FBE01-S/M-P1210	1	12X10A	440V					
FBE01-S/M-P0610-S06	1	6X10A+6XSignal(2A)	440V					
FBE01-S/M-S12	1	12XSignal(2A)	440V					
FBE01-S/M-P1810	1	18X10A	440V					
FBE01-S/M-P0610-S12	1	6X10A+12XSignal(2A)	440V					
FBE01-S/M-S18	1	18XSignal(2A)	440V					
FBE01-S/M-P2410	1	24X10A	440V					
FBE01-S/M-P0610-S18	1	6X10A+18XSignal(2A)	440V					
FBE01-S/M-P1210-S12	1	12X10A+12XSignal(2A)	440V					
FBE01-S/M-S24	1	24XSignal(5A)	440V					
FBE01-S/M-S30	1	30XSignal(6A) 440V						
FBE01-S/M-S36	1	36XSignal(5A)	440V					
FBE01-S/M-S48	1	48XSignal(5A)	440V					

## **HFE01 series Slip Rings**

Online Chat

FBE01-S/M-S60	1	60XSignal(5A	) ()	440V		
Drawings						
All parts drawings are different, de	pends on your request for	r circuits inform	ations, pls contact us			
Please write circuits num,current,quantity,delivery time or other optional requirements						
Company:	Email:		Name:	Tel:		
					SEND-TO-US	
Typical applications						
Industrial machinery-machining ce						

### **Customized on your request**

equipment, medical equipment

If you don't see what you want in this website, let us know; we may already have it designed or we will modify a design to meet your requirements. In many cases the specifications in the catalog can be changed to include bore size, circuits number, higher current/voltage, flange, lead wire length, shielding, connectors, higher speed, IP68, military grade, higher temperature, mixed with pneumatic/hydraulic capability. Please ask if you don't see exactly what you need as only a small fraction of our Rion slip rings are included in this catalog!

For a detailed outline drawing/3D modal files of a specific model number, or to request a quotation, please contact your local sales representative or send an email to sales@rionsr.com